

V-WEB SERIES

VPIP-3MIR30XVA-With Video Analytics



3 Megapixel High-Speed PTZ Camera With IR



Key Features

- 1/2.8" Progressive Scan CMOS
- 30X Optical Zoom, 16X Digital Zoom
- 2048(H) × 1536(V)/25fps
- Multiple Streams
- IR Range 120m
- Smart IR
- Low bitrate, good low-light performance
- 3D DNR, dWDR, ICR
- Video Analytics included (Perimeter , Single Virtual Fence , and Camera Tamper)
- WDR more than 100dB

Specifications	
Sensor	1/2.8" Progressive Scan CMOS
Min . illumination	Color 0.01Lux: B&W 0.001 Lux: IR ON 0 Lux
Day & Night	ICR
Shutter Speed	1/10,000-1/1s
Auto Iris	Auto/Manual
Wide Dynamic Range	dWDR
Digital Noise Reduction	2D/3D
Lens	30x module, 4.3 - 129 mm
Digital Zoom	16x
FOV	70.5" - 3.2"
IR LED	8 Pcs.
IR Range	120m (394 ft)
3D Position	Yes
Coordinate Display	Yes
Preset/Tour/Scan/Track	400/12/12/6
Pan/Tilt Speed	PTZ Speed Pan 0.4°~350°/s, Tilt 0.4°~180°/s
IMAGE	
Viedo Compression	H.264 Hight/Baseline Profile, MJPEG
Bite Rate (CBR/VBR)	100 kb - 12,000kb
Audio Compression	G.711, RAW_PCM
Max Resolution	2048x1536/30gps
Stream	Stream1 2048x1536 Stream2 1080p/720p/D1/CIF/QCIF/VGA/640X360
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
HLC	Yes
ROI	Yes
Defog	Yes
NETWORK	
Network Protocols	HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, PPoE, Unicast and Multicast supported
Alarm Trigger	Motion, Intrusion, Line Crossing, Tamper, Network disconnect, Disk alarm, O alarm
RTSP Video	Standard RFC2326, Support Quick Time/VLC Player.
Security	User security authentication, Reset, Hardware, WatchDog
Web Language	English, Chinese, Polish, Italian, Portuguese, Spanish
System Compatibility	ONVIF, CGI

V-WEB SERIES

VPIP-3MIR30XVA-With Video Analytics

3 Megapixel High-Speed PTZ Camera With IR



Accessories



Wall Mount



Pendant Mount



In-Ceiling Mount

INTERFACE	
Ethernet	11 Ethernet (10/100 Base-T) RJ-45 Connector
Audio I/O	1ch Audio in, 1ch Audio out
Alarm I/O	7ch Alarm in, 2ch Alarm out
RS485	Yes
BNC Output	Yes
Reset Button	Yes
Edge Storage	Micro SD/SDHC/SDXC slot, 64GB max.
GENERAL	
Power Supply	AC24V/2.5A
Power Consumption	40W max.
Operating Temperature	-40°C ~+70°C With Heater
Operating Humidity	0% - 90% RH
Protection	IP66, TVS6000V
Approvals	CE / FCC
Product Dimensions	205x332mm (8.07x13.07 In.)
Product Weight	4.3KG (9.47lbs)

Dimensions

